



Other Standard Features:

- ETLus listing pending
- 480V or 600V, 3 phase 60Hz power input
- 30kVA ventilared 3R transformer
- Output power options: 120Y/208V with 3-phase transformer
- NEMA 3R in-use combo enclosure with receptacles and breakers
- NEMA type 3R main disconnect switch
- Twist lock closure on rain guard panel
- 50A receptacle on select models

Applications:

- Food Processing
- Mining
- Defense
- Ship Maintenance/Construction
- Aircraft Maintenance/Construction
- Utility Maintenance
- Safety
- Chemical Processing
- Petroleum Processing

Catalog Number	Input Power				Secondary Info		Output Connections		ETL Listing
	Voltage In	Phase	Primary Connection	Transformer Size kVA	Secondary Voltage OUT	Secondary Panel MCB	Receptacles	Circuit Protection	
EJR24330CL3120	480V	3	6 ft. SOW Blunt	30kVA	120Y208V	N/A	(12) 5-20 TSlot GFCI DPLX	(12) 20A Breakers	Pending
EJR24330CL3061	480V	3	6 ft. SOW Blunt	30 kVA	120Y208V	N/A	(6) 5-20 TSlot GFCI DPLX (1) CS6369 50A	(6) 20A Breakers & (1) 50A 2P C.B.	Pending